

1. ALL DIMENSIONS SHOWN ARE EXISTING AND FOR REFERENCE AND SHALL BE VERIFIED IN FIELD.
2. ALL WORK SHALL BE CONSIDERED BASE BID, UNLESS OTHERWISE NOTED.
3. SEE SHEET 0000 FOR ADDITIONAL PROJECT GENERAL NOTES AND REQUIREMENTS.



© Copyright 2025, MCGILL SMITH PUNSHON, Inc

- 1 IN HATCHED AREA, PROVIDE COMPLETE SEAL COAT AND RE-STRIP - APPROXIMATE AREA = 615 SQUARE YARDS - FIELD VERIFY QUANTITY AND VERIFY EXISTING STRIPING PRIOR TO WORK AND REPLACE IN KIND
- 2 PROVIDE ASPHALT CRACK FILL TO A DEPTH OF 3" ON ASPHALT SURFACES CANPUS WIDE, AS REQUIRED - RE-STRIP ALL AREAS AFFECTED BY CRACK FILL - TOTAL QUANTITY OF CRACK FILL ACROSS ALL CANPUSES COMBINED SHALL BE 20,000 LINEAR FEET - REFER TO BID FORM
- 3 PRIOR TO NEW STRIPING, PROVIDE COMPLETE SEAL COAT OF EXISTING FIRE TOWER PARKING LOT - SEE PLAN FOR NEW STRIPING LAYOUT AND CONFORM WITH OWNER PRIOR TO START OF WORK - APPROXIMATE QUANTITY = 5,800 SQUARE YARDS - VERIFY QUANTITY WITH OWNER
- 4 PROVIDE NEW C&D TYPE 6 CURB AT THIS LOCATION - TIE INTO EXISTING ADJACENT CURB TO REMAIN AT DRIVE - VERIFY IN FIELD
- 5 REMOVE EXISTING ASPHALT AND BASE AND ADJACENT CURB AT EXISTING ACCESS DRIVE - PROVIDE NEW TOPSOIL TO MAKE FLUSH AND SMOOTH WITH ADJACENT LAWN AREAS - PROVIDE NEW SEED AND STRAW / AREA - CONTRACTOR SHALL WATER AND MAINTAIN NEW GRASS UNTIL FULLY ESTABLISHED
- 6 REMOVE EXISTING SIDEWALK, HANDRAIL AND SIDEWALK - REMOVE EXISTING BUSHES ON EACH SIDE OF EXISTING SIDEWALK / STAIRS
- 7 PROVIDE NEW CONCRETE SIDEWALK AND STAIRS WITH HANDRAILS ON EACH SIDE - SEE DETAILS
- 8 SEE SHEET C105 FOR NEW CROSS WALK DESIGN
- 9 AFTER NEW SEAL COAT, PROVIDE NEW STRIPING FOR SCHOOL BUS PARKING AS INDICATED - EACH SPACE TO RECEIVE STRIPING AND NUMBERING - OWNER TO ADVISE ON FINAL NUMBERING AND LAYOUT - SEE SHEET C10 FOR PROPOSED BUS LAYOUT
- 10 PROVIDE NEW 30'-0" WIDE ASPHALT ACCESS DRIVE BETWEEN PARKING LOT AND DRIVE - VERIFY GRADES FIELD AND MATCH ELEVATIONS AT PARKING LOT AND DRIVE - SEE TYPICAL ASPHALT PAVING SECTION ON SHEET C10 FOR NEW ASPHALT PROFILE - PROVIDE 18" CONCRETE PIPE UNDER DRIVE TO MAINTAIN EXISTING DRAINAGE WITH RIP RAP STONE AT EACH END OF OPENING
- 11 COMPLETELY REMOVE ALL EXISTING TREES AND SHRUBS AFFECTED BY NEW DRIVE - VERIFY IN FIELD
- 12 PROVIDE 4" DIAGONAL STRIPING AT EXISTING BUS LOOP AND PAINT EXISTING CURB IN LOOP TO MATCH - TOTAL OF FOUR (4) NEW SIGNS TO READ "PARENT PICK UP / DROP OFF ONLY" - COORDINATE LOCATION -



SCALE:  $3/4" = 1'-0"$

1

6/26

$$S(\mathcal{A}) \cap F \cap I'' = \emptyset$$


**BUTLER TECH  
FAIRFIELD CAMPUS**

3603 HAMILTON MIDDLETOWN ROAD  
HAMILTON, OHIO 45011

Project Number 06398.82  
Drawing Scale AS NOTED  
Sheet Number C106  
File Number 06398.82